



H 6500 BM

Built-in microwave combination oven

with combination operating modes and food probe for precise cooking results

- 5 line TFT clear text display with touch controls SensorTronic
- Simple cleaning cabinet with PerfectClean and linen-weave pattern
- Achieve perfect results with ease Automatic programmes
- Precise temperature controlled roasting Food probe
- Fresh popcom at the single touch of a button 'Popcorn' button

Design	
Display	SensorTronic
Retractable dials / Clear text / Symbols	-/-/-
Gourmet advantages	
Electronic temperature regulation from 25 to 250 °C	•
Electronically controlled microwave power	•
Microwave power levels: 80, 150, 300, 450, 600, 850 and 1000 W	•
Functions	
Fan plus / Fan grill / Auto roast	●/●/●
Gentle bake / Defrost / Low temperature cooking	●/●/●
Grill / Number of grill settings	●/3
Intensive bake /Conventional heat / Bottom heat	●/●/●
Microwave solo	•
Microwave with Grill and Fan grill	•
Microwave with Fan plus	•
Microwave with Auto roast	•
Automatic programmes / Sabbath mode	●/●
Wireless food probe / Food probe with cable	-/●
Special applications	•
Convenience features	
Popcorn function	•
Clock display / Date display / Minute minder	●/●/●
Start-Stop programming/Auto switch-off	●/●
Actual temperature display / Recommended temperatures	●/●
Quick start for Microwave solo	•
User programmes / Individual settings	20/●
Recommended microwave power level for each function	•
Oven door	
CleanGlass oven door / Door contact switch	●/●
Drop down door / Side hinged door	●/-

Oven cavity	
Oven capacity in I / Shelf levels embossed on oven trim	43/ -
Number of halogen lights: in roof of oven / side of oven	1/-
Easy maintenance	
Stainless steel front with CleanSteel finish	•
Stainless steel oven cavity with PerfectClean / Linen finish	●/●
Hinged grill element	•
Safety	
Appliance cooling system and cool front	•
Safety switch-off / System lock	●/●
Rapid heat-up	•
Accessories supplied	
Number of glass trays / Combi racks	1/1
Boiling rod	1
Technical data	
Total connected load in kW / Voltage V / Fuse rating A	3.2/230/20
Niche dimensions in mm (W x H x D)	560-568x448- 452x550