

# SIEMENS



## Integrated hood LE62031GB silver metallic lacquer

### Design

- 599 mm wide
- Rocker switch control
- Installation between cupboards
- Furniture door required


### Key features

- 1 x 40W bulbs
- Paper grease filter

### Performance/technical information

- Suitable for ducted and re-circulating operation
- Maximum extraction rate 280 m<sup>3</sup>/h
- Noise level at maximum normal setting: 54 dB (A); equivalent to 66 dB (A) re 1 pW according to EN 60704-2-13
- 3 x power levels


## Included accessories



## Optional accessories

- LZ23000 Paper grease filter
- LX300000 Active carbon filter

## Alternative colors available



## Technical Data

### Characteristics

Typology : Integrated  
Approval certificates : CE, VDE  
Length electrical supply cord (m) : 130.0  
Dimensions of the product, with chimney (if exists) (mm) : 380 x 599 x 280  
Net weight (kg) : 7.00  
Type of control : mechanical  
Number of speed settings : 3-stage  
Maximum output air extraction (m<sup>3</sup>/h) : 280  
Maximum output recirculating air (m<sup>3</sup>/h) : 230  
Number of lights (Stck) : 1  
Diameter of air outlet (mm) : 120  
Grease filter material : Not washable synthetic

### Consumption and connection features

Connection Rating (W) : 170  
Voltage (V) : 220-230  
Frequency (Hz) : 50  
Plug type : GB plug  
Installation typology : Instead of cabinet

Siemens  
LE62031GB  
Extractor hoods

Predecessor:

Successor:

EAN code:  
4242003267707

sales programme: